

Air Precleaners

Original Aluminum & Stainless Steel

Reduce Operating Costs
Increase Filter Life
Improve Fuel Efficiency
Reduce Emissions
Increase Engine Life

Airflow range 3 to 2000 CFM (can be manifolded for greater CFM requirements)

Self cleaning ejector system eliminates up to 97% of dirt from the air stream extending element life up to 10 times — or more!

Can be mounted in any position vertical, horizontal, even upside down!

Enginair precleaners are designed to remove most of the contaminant's from the air that feeds the engine. Not only do they extend filter life, but turbochargers, blowers, cylinder liners, piston rings, and lubricating oil are protected from extreme wear caused by contaminants reaching the engine.



Polished Aluminum Hood
Cast Aluminum body
Stainless Steel Rotor
Dual Sealed Bearings



LIFETIME WARRANTY

Precleaner Specifications

Model Number	Part Number	Air Intake (ID)		CFM		M ³ /min		Dimension				Weight	
		Inch	M.M.	Min.	Max.	Min.	Max.	Inches		Millimeters		Lbs.	Kg
		I.D.	I.D.					A	B	A	B		
200	61001	2	50.8	20	100	0.57	2.8	3.125	4.75	79.4	120.7	2	1.0
255	61005	2.5	63.5	100	200	2.8	5.7	4.25	6.00	108.0	152.4	3	1.4
330	61010	3	76.2	140	350	3.96	9.91	4.75	8.25	120.7	209.6	5	2.3
440S	61015	4	101.6	140	350	3.96	9.91	4.75	8.25	120.7	209.6	5	2.3
445	61020	4.5	114.3	300	600	8.5	17	7.125	10.63	181.0	269.9	8	3.6
550	61025	5	127.0	300	600	8.5	17	7.125	10.63	181.0	269.9	8	3.6
660S	61030	6	152.4	300	600	8.5	17	7.125	10.63	181.0	269.9	8	3.6
660	61035	6	152.4	400	850	11.3	24.1	7.125	12.25	181.0	311.2	9	4.1
770L	61045	7	177.8	500	1400	14.2	39.6	7.25	14.13	184.2	358.8	11	5.0
880	61050	8	203.2	500	1400	14.2	39.6	7.25	14.13	184.2	358.8	11	5.0
990	61055	9	228.6	900	2000	25.5	56.6	8.125	17.13	206.4	435.0	14	6.4

Caution! Precleaner selection must be based on engine airflow specifications—not on inlet tube diameter!